

Nominal power 2500 ÷ 6000 kW

Design pressure 6 bar



TNOX - TNOX.e

Three-pass boiler






The TNOX range includes three pass, wet back boilers with low thermal load in the combustion chamber (between 1 and 1.2 MW/m3). The boilers with automatic operation are suitable for operation on liquid or gaseous fuels and designed for large heating systems with an operating temperature between 60 and 100°C., Designed for 110°C maximum temperature.

TECHNICAL DATA

TNOX - TNOX.e	Heat output	Design pressure	100% Productivity (ref. P.C.I.)
	kW	bar	%
2500	2500	6	93
3000	3000	6	93
3500	3500	6	93
3500 4000	4000	6	93
5000	5000	6	93
6000	6000	6	93







Standard accessories

Optional accessories

1. Electrical panel

2. Burner

DIMENSION

TNOX - TNOX.e	н	L	Р	Empty weight	Total volume	
	mm	mm	mm	kg	TNOX	TNOX.e
2500	2460	2200	3879	6300	4496	4496
3000	2460	2200	4379	6950	5000	5746
3500	2700	2410	4379	8200	6441	6441
4000	2700	2410	4879	8970	7335	7335
5000	2820	2560	5389	11280	9088	9088
6000	2820	2560	5389	12160	10066	12160

ADVANTAGES

- Control and regulation of the
 - connection and regulation of the entire system via a PLC entirely developed by ICI.
- Interconnection with the heating plant: remotization of all operating data via communication protocols. Creation of a synoptic on a dedicated web page for remote telemanagement.
- Traditional fuels: Methane - LPG - Naphtha - Diesel
- Clean fuels: Biogas - Biomethane - Biodiesel - Syngas

• H₂ Ready:

Compatibility with hydrogen operation with mixtures up to 100%

Certifications











MAIN APPLICATIONS









SUPPORT SERVICES

With the new Assistance Services specific to the different types of generators and the impact they have on productivity, ICI Powering Evolution customers can maintain the high efficiency status of their thermal power plants.

Activity

The support services activities are grouped into 4 categories:

- Web Access Pack
- LVL 1 Basic Support
- LVL 2 Advanced Support
- LVL 3 Advanced Support Plus



ACCESSORIES AVAILABLE





ECXV KONDStainless steel vertical condensing economiser



RETURN T° CONTROL SYSTEM

System for maintaining the temperature difference Δ° between supply and return



CASCADE MASTER/SLAVE FRAMEWORK

Eterm framework for cascade management



ELECTRIC PANEL WITH PLC

System and cascade management panel with Eterm PLC



SERVICE LEVEL AGREEMENT

11 managed services, 4 levels of offering

